



■FEATURES

- ▷ Working Pressure : 10kg/cm²
- ▷ Max Temperature : 80℃
- ▷ Material : ASTM A351-CF8
ASTM A351-CF8M
- ▷ End connection : RF FLANGE
- ▷ TYPE : B.B

■ APPLICABLE STANDARDS

- ▷ Design Rating : ANSI B16.34
- ▷ Face-to-face Dimensions : API 6D
- ▷ End Flange Dimensions : ANSI B16.5

NO	PARTS NAME	METERIAL
1	NAMEPLATES	AL
2	ROUND NUT	C.S
3	HANDWHEEL	CAST IRON
4	BEARING GLAND	C.S
5	OIL CUP	BRASS
6	STEM NUT	QT
7	STEM	SUS304
8	NUT	SUS304
9	WASHER	SUS304
10	GLAND	CF8
11	SCREW	SUS304
12	PACKING	PTFE
13	BONNET	CF8
14	NUT	SUS304
15	STUD	SUS304
16	GASKET	PTFE
17	BODY	CF8
18	DISC	CF8

SIZE	D	D1	D2	D3	N-øZ	L	E	H
15A	15	34.9	60.3	90	4-16	108	120	225
20A	20	42.9	69.9	100	4-16	117	120	235
25A	25	50.8	79.4	110	4-16	127	160	255
32A	32	63.5	88.9	115	4-16	140	160	272
40A	40	73.0	98.4	125	4-16	165	180	315
50A	50	92.1	120.7	150	4-19	178	200	360
65A	65	104.8	139.7	180	4-19	190	220	425
80A	80	127.0	152.4	190	4-19	203	240	460

품질향상을 위하여 사전 예고없이 사양이 변경 될 수 있습니다.